

1. Run NovaLCT-Pluto, move the cursor over the *Advanced Login (A)* and click the button.

B NovaLCT-	Pluto V4.5.2									x
System(S)	Setting(N)	Tools(C)	er(U) Plug-	in Tool(P) La	anguage(Lang)	(L) Help(H)				
Advanced Login(A)       Brightness     Display Control   Monitor Function Card Main Board Power										
- Remote System Info - Remote Address: Pluto2012 (192.168.0.220) Net Connection: Connected Device Count: 1  Search - Monitor Info - Monitor										
<b>H</b>	-	111			8	¥			··	
			$\bigcirc$					$\bigcirc$		

## Connection Status: Connected control card

2. Login with the password "admin".

S NovaLCT-Pluto V4.5.2	<u> </u>
System(S) Setting(N) Tools(C) User(U) Plug-in Tool(P) Language(Lang)(L) Help(H)	
Brightness Display Control Monitor	
Remote System Info Remote Address: Pluto2012 (192.168.0 Password:	Search
Monitor Info	••
Connection Status: Connected control card	

## 3. Click the *Function Card* button.





4. Check the *Refresh* button.

Function Card Management				$\times$
Refresh	ower Management Monitor Data	External Device Load	Program	
	-		-	

5. Select a MFN device which you intend to operate, Click *Power* 

Management icon in right part of the window.

Function Card Management		×
Refresh	Power Management Monitor Data External Device Load Program	
	2016-08-26 Friday 10:35:25 Read Set	Start Delay
	Auto	Start All Emergency Stop
	Switch 1: Start Stop	
	Switch 2: Start Stop	
	Switch 3: Start Stop	
	Switch 4: Start Stop	
	Switch 5: Stop	
	Switch 6: Stop	
	Switch 7: Stop	
	Switch 8: Start Stop	
	2016/8/26 10:36:11Start power:Succeed	^
	2016/8/26 10:36:12Start power:Succeed 2016/8/26 10:36:12Start power:Succeed	
		✓

In this window, select *Manual*, and then could manually start/stop

corresponding power supply by click the *Start* or *Stop* button.