DAKTRONICS RC-100 PRODUCT SPECIFICATIONS



The RC-100 handheld controller is a truly wireless device that can control a variety of Daktronics standard scoreboards. For baseball/softball, the umpire operating the RC-100 unit, as well as the fans and players, can instantaneously see the ball and strike count on the scoreboard. For tennis, multiple RC-100 units can be used to control multi-court scoreboards.

The handheld controller operates one scoreboard at a time with a single scoreboard receiver. Additional receivers may be used for certain applications, such as when two play clocks are located at opposite ends of a football field.

The handheld unit operates using a 900 MHz radio with internal antenna and features 15 selectable channels to minimize radio interference. Rechargeable Ni-MH (Nickel Metal Hydride) battery provides 8-10 hours of operation on a full charge.

DIMENSIONS	WEIGHT	POWER
4.7" H x 2.7" W x 1.2" D (119 mm, 69 mm, 31 mm)	0.4 lb (0.18 kg)	 2000 mAh rechargeable Ni-MH battery Power supply for charging and/or 120 VAC operation

DISPLAY

97 x 32 graphic LCD non-backlit screen with adjustable contrast

OPERATING RANGE

10' - 500' (3 - 152 m)

CONSTRUCTION

Durable ABS plastic

OPTIONS & ACCESSORIES

- Multi-unit charger (charges up to 6 RC-100 controllers at once)
- Carrying/operation case (includes belt clip, wrist and neck strap)

FOR ADDITIONAL INFORMATION

Manual: See <u>ED-15133</u>



DAKTRONICS RC-100 PRODUCT SPECIFICATIONS

SUPPORTED SCOREBOARDS & TIMERS

BASEBALL	BASKETBALL	MULTISPORT	FOOTBALL	TIMERS
BA-618	BB-2101*	MS-915	FB-824	TI-218 (two-digit, play clock only)
BA-624	BB-2102*	MS-918*	FB-4005	TI-2003/TI-2203 (two-digit, play clock only)
BA-2010	BB-2105*	MS-2002*		TI-2010 (two-digit, play clock only)
BA-2017	BB-2106*	MS-2006*	SOCCER	TI-2012 (segment timer)
BA-2515	BB-2116*	MS-2013	SO-918	TI-2015/TI-2215 (two-digit, play clock only)
BA-2518	BB-2121*	MS-2025	SO-2918	TI-2019 (four-digit, pitch time/TOD only)
BA-2618	BB-2122	MS-2113		TI-2024 (two-digit, play clock only)
BA-2715	BB-2142	MS-3918		TI-2032 (four-digit, pitch time/TOD only)
BA-2718				Tl-2101 (four-digit)
				Tl-2102 (four-digit)
* To be controlled via RC-100, these models must NOT have			. TI-2200 (four-digit)	

^{*} To be controlled via RC-100, these models must NOT have programmable Team Name Message Centers (TNMCs) installed.

SCORING MODES



Not shown: Remote Start/Stop, Goal Judge, Rodeo

